



PREMIER POLYSTEEL

The Best Commercial Outdoor Furniture Available. Period.



Phone: 641-324-2750 • Toll Free US & Canada: 877-746-3826 • Web: www.premierpolysteel.com • Email: sales@premierpolysteel.com

Premier Polysteel Specifications for Grand Contour Swing.

Last updated June, 2017

Specifications for Grand Contour Swing

Swing Frame Post is 2" schedule 40 pipe. Swivel is galvanized cast iron with bronze bushing. Chain is 3/16" proof coil grade 30.

Expanded Metal Seat HR steel 3/4" #9 standard expanded metal

Welded Rod Seat made of .192 welded rod.

Laser Cut Steel Seat is 12 gauge HR steel.

Seat side frame is made of 1/4" HR plate, width frame made of 1/4" x 1" HR steel. All above are coated with UV and fungus resistant plastisol to a thickness of 1/8". All hardware is .305 stainless steel. **Pipe has no holes to allow access by bees or other insects.**

Specifications for Plastisol (PVC) Poly-Vinyl Chloride Coating

Material: Plastisol (PVC) shall have:

Antimicrobial (non-leaching) to help prevent microbiological attack on the plastisol (PVC) surface that can cause the loss of aesthetic appearance, mildew odors, embrittlement and premature product failure. Testing Data available Per ASTM G21-90.

Tensile strength of no less than 1800 psi per ASTM D412.

Elongation of no less than 200% per ASTM D412

Tear strength of no less than 300lb/in per ASTM D624.

Hardness of 90 ± 5 (Durometer, Shore A (Instant)) per ASTM D2240.

Flammability – Pass per FMVSS 302

UV stabilized – guaranteed to not show significant fading for 5 years per written warranty

Process: Prior to plastisol coating, each part shall be chemically washed, dried, heated and coated in a heat activated primer and dried.

After drying, each part shall be pre-heated in a convection oven to a temperature of no less than 400° F, dipped into liquid Plastisol (PVC) and cured in a convection oven at a temperature no less than 350° F. **All parts shall have a coating thickness of .125"-.25".**

Premier Polysteel products are completely plastisol coated (frames and legs included) with a thick, UV stabilized, mold and mildew resistant plastisol coating which is compliant with worldwide standards. Premier Polysteel is committed to being an environmentally conscious company and recognizes the importance of being committed to continually finding ways to support our environment.