



PREMIER POLYSTEEL

The Best Commercial Outdoor Furniture Available. Period.



Phone: 641-324-2750 • Toll Free US & Canada: 877-746-3826 • Web: www.premierpolysteel.com • Email: sales@premierpolysteel.com

Premier Polysteel Specifications Picnic Table—all mounts and Styles.

Last updated July 2023

Specifications for Rectangle and Oval Picnic Table

Table Top and Seat: HR steel 3/4" #9 standard expanded metal or 14 gauge perforated steel. Seat measures 10" across. Attached perimeter frame and supporting structure is made from HR steel. A 2" schedule 40 pipe is welded in the center of top. When coated will accept a 1.625" diameter umbrella pole (except 10' and single ped direct bury).

Free Standing Legs: Completely sealed pipe that measures 1.90" OD prior to plastisol (PVC) coating. Leg diagonal brace is made of pipe that measures 1.05" OD prior to plastisol (PVC) coating.

Double Pedestal Direct Bury Double Pedestal stand vertical posts are made of 4" pipe, arms are made of 3" pipe. Bottom of post is sealed and has horizontal 1/2" rebar extensions for securing in concrete.

Single Pedestal Direct Bury Table T-Post is made of 4" pipe, table support arm is 4" square tube, seat arms are 2" square tube. Bottom of post is sealed and has horizontal 1/2" rebar extensions for securing in concrete.

Multi Pedestal Direct Bury Table post is made of 4" pipe. Seat Post is made of 3" pipe. Bottom of post is sealed and has horizontal 1/2" rebar extensions for securing in concrete.

Multi Pedestal Surface Mount Table post is made of 4" pipe. Seat Post is made of 3" pipe. Bottom of surface mount posts have 8" dia. mounting plates.

Double Pedestal Surface Mount Double Pedestal stand vertical posts are made of 4" pipe, arms are made of 3" pipe. Bottom of surface mount posts have 8" dia. mounting plates with gussets.

Single Pedestal Surface Mount Table T-Post is made of 4" pipe, table support arm is 4" square tube, seat arms are 2" square tube. Bottom of surface mount post has four mounting feet.

All above are plastisol coated with UV and fungus resistant oven cured plastisol to a thickness of approximately 1/8". All Hardware is .304 stainless steel. **Pipe has no holes to allow access by bees or other insects.**

Specifications for Square and Round Picnic Table

Top and Seat: HR steel 3/4" #9 standard expanded metal or 14 gauge perforated steel. Seat measures 10" across. Attached perimeter frame and supporting structure is made from HR steel. A 2" schedule 40 pipe is welded in the center of top. When coated will accept a 1.625" diameter umbrella pole (free standing only).

Free Standing Legs: Completely sealed pipe that measures 1.66" OD prior to plastisol (PVC) coating.

X Brace is HR steel.

Direct Bury Center Post: 4" square tube; Top of pipe is sealed. Bottom of pipe is sealed and has horizontal .5" rebar extensions for securing in concrete. Seat and Top supports are made of 2" square tubing. The 2" tube is plastisol coated to approximately 2-3/8" OD. Seat arms are made of 4" OD square tubing. No umbrella hole on Direct Bury.

Multi Ped Direct Bury Table post is made of 4" pipe. Seat Post is made of 3" pipe. Bottom of post is sealed and has horizontal 1/2" rebar extensions for securing in concrete.

All above are plastisol coated with UV and fungus resistant oven cured plastisol to a thickness of approximately 1/8". All hardware is .304 stainless steel. **Pipe has no holes to allow access by bees or other insects.**

Specifications for Square and Rectangle Kid's Picnic Table

Top and Seat: HR steel 3/4" #9 standard expanded metal or 14 gauge perforated steel. Seat measures 10" across. Attached perimeter frame and supporting structure is made from HR steel. A 2" schedule 40 pipe is welded in the center of top. When coated will accept a 1.625" diameter umbrella pole (free standing only).

Free Standing Legs: Completely sealed pipe that measures 1.66" OD or 1.90" OD prior to plastisol (PVC) coating.

X Brace (on square kid's table only) is HR steel.

Pipe has no holes to allow access by bees or other insects.

Specifications for Plastisol (PVC) Polyvinyl Chloride Coating

Material: Plastisol (PVC) shall have:

Antimicrobial (non-leaching) to help prevent microbiological attack on the plastisol (PVC) surface that can cause the loss of aesthetic appearance, mildew odors, embrittlement and premature product failure. Testing Data available Per ASTM G21-90.

Tensile strength of no less than 1800 psi per ASTM D412.

Elongation of no less than 200% per ASTM D412

Tear strength of no less than 300lb/in per ASTM D624.

Hardness of 90 ± 5 (Durometer, Shore A (Instant)) per ASTM D2240.

Flammability – Pass per FMVSS 302

UV stabilized – guaranteed to not show significant fading for 5 years per written warranty

Process: Prior to plastisol coating, each part shall be chemically washed, dried, heated and coated in a heat activated primer and dried.

After drying, each part shall be pre-heated in a convection oven to a temperature of no less than 400° F, dipped into liquid Plastisol (PVC) and cured in a convection oven at a temperature no less than 350° F. **All parts shall have a coating thickness of .125"-.25".**

Premier Polysteel products are completely plastisol coated (frames and legs included) with a thick, UV stabilized, mold and mildew resistant plastisol coating which is compliant with worldwide standards. Premier Polysteel is committed to being an environmentally conscious company and recognizes the importance of being committed to continually finding ways to support our environment.

Premier Polysteel is a division of ADA Enterprises, Inc.